



FIBERGLASS LONG-THROW MULTICELL HORN SPEAKER

H 6045



Fiberglass horn designed to withstand the most adverse weather conditions, offering high sound reproduction quality and sound pressure levels.

A high level of efficiency and sound pressure can be obtained thanks to the use of four dynamic driver units.

- **Specifications**
- **Accessories**
- **APPLICATIONS**
- Car parking
- Bathing establishment
- Stadium
- Funny resort

PART NUMBER

13120011

FEATURES

- Long-throw horn speaker
- Body in RAL 9003 white fiberglass
- -3/8" W - 18 N threaded connector for driver unit
- 1 Attachment bracket
- Watertight construction
- Use with up to 4 driver D 5076
- Use with up to 4 transformer TD 507 for constant voltage line

ACOUSTICAL SPECIFICATION

- Type of speaker: **Rectangular to be combined with 4 drivers model D 5076**
- Frequency Response: **150 Hz ÷ 12 kHz**
- Max SPL @ 1m: **132 dB**
- Horizontal coverage angle: **60°**
- Vertical coverage angle: **50°**
- Power Handling: **200 W RMS**
- Peak Power Handling: **300 W PEAK**
- System Sensitivity: **101 dB**
- Impedance: **16 Ω**

INPUT SECTION

- Input connector:**2 conductor cable, 1 meter length**
- Constant voltage:**100 V , 70 V , 25 V**
- Power Selection:**50 - 25 - 12 - 6 W**

CABINET

- Hardware:**Body in fibreglass, RAL 9003 grey**
- Colour:**Grey**

PHYSICAL SPECIFICATIONS

- Height:**560 / 22.04 mm/inch**
- Width:**475 / 18.7 mm/inch**
- Depth:**620 / 24.4 mm/inch**
- Net weight:**9.67 / 21.31 kg/lbs**

SHIPPING INFORMATION

- Package height:**645 / 25.39 mm/inch**
- Package width:**615 / 24.21 mm/inch**
- Package depth:**895 / 35.23 mm/inch**
- Shipping weight:**12.45 / 27.44 kg/lbs**